

Oil Mi\$er

**ON-DEMAND
WATER HEATER**

**SAVE MONEY!
ONLY HEAT WATER WHEN YOU NEED IT!
NEVER RUN OUT OF HOT WATER, AGAIN!**



OM-148

TOYOTOMI

COOLING-HEATING PRODUCTS



Model:	OM-148 Water Heater
Ignition:	High Voltage Discharge Spark
Fuel Type:	No. 2 Fuel Oil [Typical Home Heating Oil] or No. 1 Fuel Oil (ASTM D396)
Efficiency:	88 %
Heat Rating:	148,000 BTU/h
Fuel Consumption:	1.05 gal./h
Fuel System:	Oil tank ⁽¹⁾
Maximum Hot Water Temperature:	155 °F (approximately)
Water Flow Rate/ Temperature Rise:	6.1 gal./min (40 °F rise) 4.8 gal./min (50 °F rise) 4.0 gal./min (60 °F rise) 3.5 gal./min (70 °F rise) 3.0 gal./min (80 °F rise)
Capacity of Heat Exchanger:	5.1 gal
Dimensions (W x H x D):	12-5/8" x 27-3/4" x 22-1/2"
Weight:	86 lbs. (Empty)
Vent Pipe Hole:	4-3/4" (Diameter)
Maximum Length of Flue Vent Pipe System:	10 ft., 3 bends or less
Maximum Length of Chimney:	26 ft.
Electrical Rating:	120 Volts AC, 60Hz Ignition: 120 Watts Burning: 98 Watts
Required Accessories:	In-line fuel filter Temp & pressure relief valve Flue pipe installation kit or Chimney installation adapter kit
Safety Devices:	Over-heat protector Ignition safety device Empty burning protective device Heat exchanger bi-metal switch Temperature fuse, Fusible link valve

The Toyotomi water heater is on-demand which means there is no costly storage of hot water when it is not needed. And like all Oil Miser products, it's safe, reliable and easy to install.

Shower yourself with savings year after year. Ask your local dealer about the Oil Miser® Water Heater today.

- Heats up to 240 gallons per hour!
- **SAVE MONEY**
(average payback: 24 to 30 months!)
- Stainless steel heat exchanger!
- 88% efficient!
- Safe: UL, CUL, home and mobile home approved!
- Direct vent (as shown below) or chimney vent!

(1) Existing oil tank or purchase tank from local supplier.

TOYOTOMI U.S.A., Inc.

604 Federal Road
Brookfield, Connecticut 06804-0176
Telephone (203) 775-1909 • Fax (203) 775-6330
www.toyotomiusa.com

